

Super White Gloss/FT60L/WK80

PHYSICAL CHARACTERISTICS

Facestock

A super white and glossy surface, one side cast coated, mirror-finished printing paper. This paper has excellent wet strength, bulk and whiteness. Offers top print quality by letterpress, offset, flexo, screen in single or multi-color lines.

Basis weight ISO 536 : 80 gsm
Caliper ISO 534 : 88 μ m

Adhesive

A general purpose emulsion acrylic removable adhesive with good initial tack and superior removability. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing as well as ECC 88/378/EEC, CEN EN71, PART 3.

Minimum Application Temperature : -5°C
Product Functional Service Temperature: -20°C / +80°C

Liner

A white densified clay coated kraft paper.

Basis weight ISO 536 : 80 gsm
Caliper ISO 534 : 80 μ m

PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	2.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM1	1.5 N/25mm (20mins)
Total Product Caliper	ISO 534	171 μ m

Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.