

## SWG80/FT62W/C2S90

### PHYSICAL CHARACTERISTICS

#### Facestock

A super white and glossy surface, one side cast coated, mirror-finished printing paper. This paper has excellent wet strength, bulk and whiteness. Offers top print quality by letterpress, offset, flexo, screen in single or multi-color lines.

Basis weight ISO 536 : 80 gsm  
Caliper ISO 534 : 88  $\mu\text{m}$

#### Adhesive

A general purpose emulsion acrylic removable adhesive with good initial tack and superior removability. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing as well as ECC 88/378/EEC, CEN EN71, PART 3.

Minimum Application Temperature :  $-12^{\circ}\text{C}$   
Product Functional Service Temperature:  $-30^{\circ}\text{C} / +80^{\circ}\text{C}$

#### Liner

A white densified double side coated kraft liner.

Basis weight ISO 536 : 90 gsm  
Caliper ISO 534 : 82  $\mu\text{m}$

### PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	1.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM1	1.5 N/25mm (20mins)
Total Product Caliper	ISO 534	183 $\mu\text{m}$

#### Shelf life

1 year when stored at  $22^{\circ}\text{C}$  and 50% RH