

## Gloss Art 150/FT60W/C2S90

### PHYSICAL CHARACTERISTICS

#### Facestock

A white and glossy machine coated super-calendered woodfree printing paper. The coated facestock offers top print quality by all conventional printing processes.

Basis weight ISO 536 : 150 gsm  
Caliper ISO 534 : 110 µm

#### Adhesive

A general purpose emulsion acrylic removable adhesive with good initial tack and superior removability. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing as well as ECC 88/378/EEC, CEN EN71, PART 3.

Minimum Application Temperature : -5°C  
Product Functional Service Temperature: -20°C / +80°C

#### Liner

A white densified double side coated kraft liner.

Basis weight ISO 536 : 90 gsm  
Caliper ISO 534 : 82 µm

### PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	2.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM2	1.5 N/25mm (20mins)
Total Product Caliper	ISO 534	200 µm

#### Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.