

TECHNICAL INFORMATION



Gloss Art150/FT61L/WK120

PHYSICAL CHARACTERISTICS

Facestock

A white and glossy machine coated super-calendered woodfree printing paper. The coated facestock offers top print quality by all conventional printing processes.

Basis weight ISO 536 : 150 gsm
Caliper ISO 534 : 118 µm

Adhesive

An emulsion acrylic ultra-removable adhesive designed for superior removability on a wide variety of substrates. Features good initial tack. Meets US FDA indirect food contact requirements (21 CFR 175.105).

Minimum application temperature : +5°C
Product Functional Service temperature : -20°C / + 80°C

Liner

A white densified clay coated kraft paper.

Basis weight ISO 536 : 120 gsm
Caliper ISO 534 : 113 µm

PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	2.3 N/25mm
Adhesion to Stainless Steel	FINAT FTM1	2.0 N/25mm (20mins)
Total Product Caliper	ISO 534	240 µm

Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.