

TECHNICAL INFORMATION



Gloss Art150/FT61W/C2S90

PHYSICAL CHARACTERISTICS

Facestock

A white and glossy machine coated super-calendered woodfree printing paper. The coated facestock offers top print quality by all conventional printing processes.

Basis weight ISO 536 : 150 gsm
Caliper ISO 534 : 110 µm

Adhesive

An emulsion acrylic ultra-removable adhesive designed for superior removability on a wide variety of substrates. Features good initial tack. Meets US FDA indirect food contact requirements (21 CFR 175.105).

Minimum application temperature : +5°C
Product Functional Service temperature : -20°C / + 80°C

Liner

A white densified double side coated kraft liner.

Basis weight ISO 536 : 90 gsm
Caliper ISO 534 : 82 µm

PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	2.3 N/25mm
Adhesion to Stainless Steel	FINAT FTM1	2.0 N/25mm (20mins)
Total Product Caliper	ISO 534	201 µm

Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.

Code: Y01042013
Rev00