

## Super Vellum70/FT62W/C2S90

### PHYSICAL CHARACTERISTICS

#### Facestock

A matte brilliant white woodfree machine finished printing paper with good opacity and superior toner bonding. It can be printed by all conventional printing processes. Designed to suit sheet prints for office monochrome copiers and laser printers.

Basis weight ISO 536 : 70 gsm  
Caliper ISO 534 : 88  $\mu$ m

#### Adhesive

A general purpose emulsion acrylic removable adhesive with good initial tack and superior removability. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing as well as ECC 88/378/EEC, CEN EN71, PART 3.

Minimum Application Temperature : -12°C  
Product Functional Service Temperature: -30°C / +80°C

#### Liner

A white densified double side coated kraft liner.

Basis weight ISO 536 : 90 gsm  
Caliper ISO 534 : 82  $\mu$ m

### PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	2.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM1	1.5 N/25mm (20mins)
Total Product Caliper	ISO 534	178 $\mu$ m

#### Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.