

- Car Window Label -

SWG80/MT01N/WG62

PHYSICAL CHARACTERISTICS

Facestock

A super white and glossy surface, one side cast coated, mirror-finished printing paper. This paper has excellent wet strength, bulk and whiteness. Offers top print quality by letterpress, offset, flexo, screen in single or multi-color lines.

Basis weight ISO 536 : 80 gsm
Caliper ISO 534 : 88 µm

Adhesive

An emulsion acrylic removable adhesive, with excellent aging resistance. Specially designed for clean removal from car window shields.

Minimum Application Temperature : +5°C
Product Functional Service Temperature: -5°C / +65°C

Liner

A super-calendered white glassine paper.

Basis weight ISO 536 : 58 gsm
Caliper ISO 534 : 51 µm

PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	2.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM1	0.9 N/25mm (20mins)
Total Product Caliper	ISO 534	146 µm

Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.