

TECHNICAL INFORMATION PRELIMINARY



- Garment L. -

Super Vellum70/GL01N/WG62

PHYSICAL CHARACTERISTICS

Facestock

A matte brilliant white woodfree machine finished printing paper with good opacity and superior toner bonding. It can be printed by all conventional printing processes. Designed to suit sheet prints for office monochrome copiers and laser printers.

Basis weight ISO 536 : 70 gsm
Caliper ISO 534 : 88 μ m

Adhesive

A general purpose emulsion acrylic adhesive with good initial tack and superior clean removability on various fabrics such as polyester, cotton, wool.

Minimum Application Temperature : +5°C
Product Functional Service Temperature: -30°C / +65°C

Liner

A super-calendered glassine paper.

Basis weight ISO 536 : 60 gsm
Caliper ISO 534 : 54 μ m

PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	13~14 N/25mm
Adhesion to Stainless Steel	FINAT FTM2	7~8 N/25mm (20mins)
Total Product Caliper	ISO 534	154 μ m

Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.

Code: Y29072014
Rev00