

# TECHNICAL INFORMATION PRELIMINARY



- Garment L. -

## Gloss White BOPP60 TC/GL01N/WG62

### PHYSICAL CHARACTERISTICS

#### Facestock

A bright gloss white, top-coated BOPP film. Can be printed by letterpress, screen, flexo and gravure, using UV or solvent-based inks.

Caliper            ISO 534            : 60  $\mu$ m

#### Adhesive

A general purpose emulsion acrylic adhesive with good initial tack and designed for a clean removability on rough surface garment such as wool, knitted, etc.

Minimum Application Temperature        : +5°C  
Product Functional Service Temperature: -30°C / +65°C

#### Liner

A super-calendered glassine paper.

Basis weight    ISO 536            : 60 gsm  
Caliper            ISO 534            : 54  $\mu$ m

### PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	12.0 ~ 14.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM2	7.0 ~ 8.0 N/25mm (20mins)
Total Product Caliper	ISO 534	131 $\mu$ m

#### Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.

Code: Y29072014  
Rev00