

TECHNICAL INFORMATION PRELIMINARY



- Garment L -

Crystal Clear BOPP50 TC/GL01P/WK80

PHYSICAL CHARACTERISTICS

Facestock

An ultra-clear, top-coated BOPP film. It can be printed by letterpress, screen, flexo and gravure, using UV, solvent or water-based inks.

Caliper ISO 534 : 51 μ m

Adhesive

A general purpose emulsion acrylic adhesive with good initial tack and superior clean removability on various fabrics such as polyester, cotton, wool.

Minimum Application Temperature : +5°C
Product Functional Service Temperature: -30°C / +65°C

Liner

A white densified clay coated kraft paper.

Basis weight ISO 536 : 80 gsm
Caliper ISO 534 : 75 μ m

PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	12.0 ~ 14.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM2	7.0 ~ 8.0 N/25mm (20mins)
Total Product Caliper	ISO 534	143 μ m

Shelf life

1 year when stored at 22°C and 50% RH

The information given above are based on typical measured values; they are subject to technical changes and improvements without prior notice. It is the user's responsibility to check, prior to use, whether the product is suitable for the intended application.

Code: Y11042016
Rev01